



Instructions for FLU101 and FLU102

For Your Safety

To prevent damage to your light or injury to others, please read the following safety precautions in its entirety before using this equipment. Keep these safety instructions where all those who use this equipment will read them.

Do not disassemble or modify

This light contains high voltage components. Failure to observe this precaution may result in electric shock and/or product malfunction. Should the light break open as the result of a fall or other accident, be sure to disconnect the power and take the light to an authorized maintenance center for inspection.

Keep Dry

Do not handle with wet hands. This light should not be immersed in or exposed to water or rain. Failure to observe this precaution could result in fire or electric shock.

Keep out of reach of children

This light contains small parts that may pose a choking hazard. Consult a physician immediately if a child swallows any part of this light.

Do not expose to high temperatures

Do not leave this light in a closed vehicle, in direct sunlight, or in other areas subject to extreme heat. Failure to observe this precaution could result in fire or damage to the casing or internal components.

Caution

1. Although fluorescent lamps run at much cooler temperatures than tungsten or halogen lamps, these lamps may still be very hot to the touch after prolonged use. Lamps should be allowed to cool for at least five minutes prior to stowing. Failure to do so could lead to personal injury and/or unit failure.
2. Be sure not to touch the glass tubing of the fluorescent lamps. Oils from your fingers will shorten the life of the lamp. Use gloves or a cloth when handling the lamps.
3. Avoid sudden impacts as this can damage the head and/or lamps.
4. Use only the supplied lamps, or specified replacement lamps (FLU30). Lamps should not exceed 30W of maximum power each.
5. When not in use, disconnect from the power supply.

Inserting the Lamp

Using either gloves or a clean cloth, screw in the lamp by rotating in a clockwise motion until the lamp is snug. Do not attempt to over-tighten as this can damage the lamp and/or the socket.

Attaching to the Light Stand

Loosen the light stand locking knob at the base of the light and place the assembled light on top of the stand. Re-tighten the adjustment knob to secure the unit in place.

Adjusting the Head Angle

Turn the tilt adjustment knob counter-clockwise to loosen the bracket and allow the lamp head to tilt up and down. Position the head where desired and turn the tilt adjustment knob clockwise to secure the head in place. Do not over-tighten as this could damage the bracket.

Turning on the Light

To turn on the light, start by plugging the light into a 110v/60Hz AC power outlet. Then click the inline toggle switch on the power cord to turn on the lamp.

Setting up the Shooting Tent *(FLU102 only)*

For a detailed instructional video on how to set up the 24" Pop-Up Shooting Tent, please visit the product page on the Interfit Photographic website.



Interfit Photographic
www.interfitphotographic.com
support@interfitphotographic.com

